

## **ENQUIRY/ORDER FORM**

FOR NOS EMERGENZAMATIC DEVICES TO INSTALL IN HYDRAULIC LIF I
INQUIRY / ORDER NO.: DATE: REQUEST OF DELIVERY:
LIFT REFERENCES (NUMBER, JOB, ETC):
COMPANY:
NAME & EMAIL ADDRESS OF COMPANY'S EXPERT:
CONSIGNEE ADDRESS:
TECHNICAL SPECIFICATIONS OF LIFT
Liftcar load Kg Speed m/sec: Single phase voltage available for battery charger: Volt
Stops Nos.: Longest distance between two consecutive floors mt.:
ELECTRIC EMERGENCY DESCENT VALVE: Volt: DC AC
LIFTCAR DOOR OPERATOR: Type:
THREE-PHASE DC AC SINGLE-PHASE + DRIVER DC + DRIVER
Volt: Ampere: one entrance  two entrances
The door motor is powered during the running of the lift:
RETIRING CAM (if any): Volt: Ampere: DC AC THREE-PHASE
SAFETY CIRCUITS: Volt:
PERFORMANCE REQUESTED TO THE DEVICE
COMPLETE RESCUE (DESCENT + DOOR OPENENING)
DOOR OPENING ONLY
DESCENTONLY
OPTIONS & ACCESSORIES REQUIRED FOR THE DEVICE:
SET OF BATTERIES:
INDICATOR INSIDE LIFTCAR YES NO LANGUAGE FOR MANUAL AND DRAWINGS